

Estimation of Boundary Properties Using Stochastic Differential Equations and COMSOL

Atalla A¹ and Jeremic A²

Electrical and Computer Engineering Department, McMaster University, Canada

¹ mohamasm@mcmaster.ca ² jeremic@ece.mcmaster.ca

Abstract

The inverse diffusion problems deal with the estimation of many crucial parameters such as the diffusion coefficient, source properties, and boundary conditions. Such algorithms are widely applied in many design problems in different physical [1–4], chemical [5–11], and biological fields [12]. Recently, the estimation of the boundary properties, of the diffusion process, have attracted researchers [1, 2]. However, due to the complexity of the problem, the work accomplished is not yet satisfactory. On the other hand, most of the analytical and numerical methods proposed for such problems have only been used to deal with one- or at most two-dimensional problems with simple and symmetric geometries. Limited work has been achieved on three-dimensional problems, at which simplified problems are solved. Moreover, the major purpose was to estimate the properties of a pre-determined boundary position. Nevertheless, they only account for the classical nature of the diffusion, neglecting its stochastic (random) nature described by the stochastic differential equations (SDE) and the Fokker-Planck equation [13].

Our previous work [7, 8, 10] did not deal with boundaries. In this paper we extend previous results and propose a model that can deal with arbitrary boundaries. We are addressing the issue where we estimate the absorption property of the boundary. We propose a computationally efficient framework for estimating the boundary properties using stochastic differential equations. The main advantage of this technique lies in the fact that it accounts for both drift and random effects such as Brownian motion which are not accounted for in commonly used classical techniques based on Fick's law of diffusion. The extension to realistic geometry is straightforward since it can be dealt with using Finite Element Method. Absorbing and reflecting boundaries are often encountered in realistic problems such as drug delivery where the organ surfaces represent reflecting/absorbing boundaries for the dispersion of drug particles.

In this work, we introduce a Fokker-Planck based algorithm in order to estimate the position and the length of the absorbing region of the boundary. We first utilize Fokker-planck equation with the corresponding boundary conditions to derive the forward model, at which, we utilize the COMSOL Multiphysics package to solve for the position density function of the particle undergoing diffusion. Next, we deduce the corresponding statistical model for the measurement of the number of particles. Finally, we show numerical examples to illustrate the proposed algorithm.

References

- [1] C. Yang et al. The boundary estimation in two-dimensional inverse heat conduction problems. *Journal of Physics D: Applied Physics*, 29:333–339, 1996.
- [2] C. Yang et al. Inverse estimation of the boundary condition in three-dimensional heat conduction. *Journal of Physics D: Applied Physics*, 30:2209–2216, 1997.
- [3] EH Shiguemori, FP Harter, H.F.C. VELHO, JDS da Silva, and B. SP. Estimation of boundary conditions in conduction heat transfer by neural networks. *Tendencias em Matematica Aplicada e Computacional*, 3(2):189–195, 2002.
- [4] PN Vabishchevich. Numerical solution of the inverse problem of heat conduction by using regularized difference schemes. *Journal of Engineering Physics and Thermophysics*, 49(6):1446–1449, 1985.
- [5] A. Nehorai, B. Porat, and E. Paldi. Detection and localization of vapor-emitting sources. *IEEE Transactions on Signal Processing*, 43(1):243–253, 1995.
- [6] B. Porat and A. Nehorai. Localizing vapor-emitting sources by moving sensors. In *Signals, Systems and Computers, 1994. 1994 Conference Record of the Twenty-Eighth Asilomar Conference on*, volume 2.
- [7] A. Jeremic and A. Nehorai. Design of chemical sensor arrays for monitoring disposal sites on the ocean floor. *IEEE Journal of Oceanic Engineering*, 23(4):334–343, 1998.
- [8] A. Jeremic and A. Nehorai. Landmine detection and localization using chemical sensor array processing. *IEEE Transactions on Signal Processing*, 48(5):1295–1305, 2000.
- [9] M. Ortner, A. Nehorai, and A. Jeremic. Biochemical transport modeling and bayesian source estimation in realistic environments. *IEEE Transactions on Signal Processing*, 55(6 Part 1):2520–2532, 2007.

- [10] A. Atalla and A. Jeremic. Localization of chemical sources using stochastic differential equations. In *IEEE International Conference on Acoustics, Speech and Signal Processing, 2008. ICASSP 2008*, pages 2573–2576, 2008.
- [11] L.R. Townley and J.L. Wilson. Estimation of boundary values and identification of boundary type for numerical models of aquifer flow. *Transport in Porous Media*, 4(6):567–584, 1989.
- [12] H. Terayama, K. Okumura, K. Sakai, K. Torigoe, and K. Esumi. Aqueous dispersion behavior of drug particles by addition of surfactant and polymer. *Colloids and Surfaces B: Biointerfaces*, 20(1):73–77, 2001.
- [13] H. Risken. *The Fokker-Planck equation: Methods of solution and applications*. Springer, 1989.